



DLMPort System Charts for Canon RF Mount

PORT OPTIONS

Some lenses have more than one port option. The first column is always the recommended option for the best compromise of imaging quality, performance, and handling with any given lens.

PRODUCT(S) REQUIRED

Where multiple lines of products are listed for a given option, all products listed are required to make a complete compatible lens port.

The DLM 8" Dome Port # 5516.82 may be substituted with the Modular 8" Dome for FL Systems # 5510.45 + DLM Adapter for Modular 8" Dome # 5516.80 in all instances.

LENSES REFERENCING "+4 DIOPTER REQUIRED"

A +4 diopter is available for purchase through your local camera store, and is commonly sold in a set with +1 and +2 close-up lenses. Common brands include Tiffen and Hoya. Make sure to purchase the correct size for your lens. The thread diameter is usually referenced on the front of the lens in millimeters (ø 58mm, 67mm, etc.). All photos will be out of focus if a +4 diopter is required but not used.

Canon RF Lenses

	OPTION 1 (Recommended)	OPTION 2	OPTION 3
8-15 mm Canon EF f/4L Fisheye USM + Canon EF-to-RF Adapter	The only port option that supports zoom. AF Only. Product(s) required 5516.16 Dome Port 5515.12 Zoom Gear	Zoom not supported. Lens must be used at a fixed focal length. AF Only. Product(s) required 5516.82 Dome Port	
10-17 mm Tokina AT-X f/3.5-4.5 DX Fish-eye + Canon EF-to-RF Adapter	Use zoom clamp without foam strips. AF Only. Product(s) required 5516.15 Dome Port 5509.30 Extension		
16 mm Canon RF f/2.8 STM	AF Only. Product(s) required 5516.11 Dome Port		
18-45 mm Canon RF-S f/4.5-6.3 IS STM	AF Only. Product(s) required 5516.15 Dome Port 5515.22 Zoom Gear		
18-150 mm Canon RF-S f/3.5-6.3 IS STM	Superior edge sharpness compared to shorter port options. AF Only. Product(s) required +4 Diopter Required 5516.16 Dome Port 5516.65 Extension	A longer port is recommended for better edge sharpness. AF Only. Product(s) required +4 Diopter Required 5516.15 Dome Port 5516.65 Extension	Zoom not supported. Lens must be used at a fixed focal length. AF Only. Product(s) required +4 Diopter Required 5516.82 Dome Port 5516.65 Extension
24 mm Canon RF f/1.8 Macro IS STM	AF Only. Product(s) required 5516.12 Dome Port	AF Only. Product(s) required 5516.11 Dome Port	
60 mm Canon EF-S f/2.8 Macro USM + Canon EF-to-RF Adapter	AF Only. Product(s) required 5516.45 Flat Port 5516.65 Port Extension		

	OPTION 1 (Recommended)	OPTION 2	OPTION 3
100 mm Canon RF Macro IS USM	AF Only. <u>Product(s) required</u> 5516.50 Flat Port (2) 5516.65 Extension		
100 mm Canon EF f/2.8L Macro IS USM + Canon EF-to-RF Adapter	AF Only. <u>Product(s) required</u> 5516.50 Flat Port (2) 5516.65 Extension		